(Chonbuk National Economic Development Agency 3F) Palbok-dong 1, Deokjin-gu, Jeonju, Korea

T: +82-63-211-2284 F: +82-63-214-2283

www.katri.re.kr



## TEST REPORT

APPLICANT: IRI FACTORY VINA

**BUYER** 

KATRI NO

: JJHA22-00000216

RECEIVED DATE: NOV. 18, 2022

ISSUED DATE : DEC. 23, 2022

PAGE(S)

: 1 OF 2

APPLICANT'S PROVIDED SAMPLE DESCRIPTION S/# : Scaffolding Net 101g

TECT LIEM	TEST RESULT
TEST ITEM	#1
Light Blocking (%): KS K 0819:2018 Method B	
	35.93
<note> Applicant's Requested Test Method.</note>	
Air Permeability (cm²/cm²·s) : ASTM D 737-2018 Pressure Differer	ntial : 125 Pa
	1 300
<note> 1. Test surface area : 20 cm²</note>	
2. Pressure drop : 100 Pa	
3. Applicant's Requested Test Method.	

- Continues -

Lim, Hun Jin Director General

Technical Manager : Hong Jae Yong Tested by Name: Shon Young Hae

Location of Test: Wangsan-ro 51, Yongdu-dong, Dongdaemun-gu, Seoul, Korea







(Chonbuk National Economic Development Agency 3F) Palbok-dong 1, Deokjin-gu, Jeonju, Korea

T: +82-63-211-2284 F: +82-63-214-2283

www.katri.re.kr



KATRI NO: JJHA22-00000216

PAGE(S): 2 OF 2

#1

Weatherability (GRADE): ASTM G 154-16

Colour Fastness 4-5

Appearance change NO MELTING AND SHATTERING

<Note> 1. EXPOSURE CYCLE : CYCLE 1.

LAMP:UVA-340

EXPOSURE PERIOD: 8 H UV AT (60±3)℃

BLACK-STANDARD TEMPERATURE 4H CONDENSATION AT  $(50\pm3)$  BLACK-STANDARD TEMPERATURE IRRADIANCE :  $0.89~\text{W/m}^2$  AT 340~nm

2. EXPOSURE TIME: 200 h

3. THE TEST WAS CONDUCTED WITH GRAY SCALE(KS K ISO-A02:2014) BY CLIENT'S REQUEST.

4. MELTING AND SHATTERING WERE OVSERVED BY CLIENT'S REQUEST.

5. TEST ORGANIZATION: FITI

#1